

CLEAR EDGE GLASS - [AS1288 - Supp1-2006 Two Edge Support Table]

Ultimate Limit State [ULS] Pressure [Pa] - General														
Wind Class		Wind load Pa	System Height mm											
C	N		1590	1740	1890	2040	2190	2340	2490	2640	2790	2940	3090	3240
	1	700											10	10
	1	800										10	10	10
	2	900									10	10	10	10
	2	1000							10	10	10	10	10	12
	2	1100						10	10	10	10	10	12	12
	2	1200						10	10	10	10	12	12	12
	2	1300						10	10	10	12	12	12	15
	3	1400						10	10	12	12	12	12	15
	3	1500					10	10	10	12	12	12	15	15
	3	1600					10	10	10	12	12	15	15	15
	3	1700				10	10	10	12	12	15	15	15	15
1	3	1800				10	10	10	12	12	15	15	15	15
1	3	1900				10	10	12	12	12	15	15	15	
1	4	2000			10	10	10	12	12	12	15	15	15	
1	4	2100			10	10	10	12	12	15	15	15		
1	4	2200			10	10	12	12	12	15	15	15		
1	4	2300			10	10	12	12	15	15	15	15		
1	4	2400			10	10	12	12	15	15	15			
1	4	2500		10	10	10	12	12	15	15				
1	4	2600		10	10	12	12	12	15	15				
2	4	2700		10	10	12	12	15	15	15				
2	4	2800		10	10	12	12	15	15	15				
2	4	2900		10	10	12	12	15	15	15				
2	5	3000	10	10	10	12	15	15	15					
2	5	3100	10	10	12	12	15	15	15					
2	5	3200	10	10	12	12	15	15	15					
2	5	3300	10	10	12	12	15	15	15					
2	5	3400	10	10	12	12	15	15	15					

2	5	3500	10	10	12	12	15	15						
2	5	3600	10	10	12	15	15	15						
2	5	3700	10	12	12	15	15	15						
Max Panel width [mm]		10	850	850	850	850	850	850	850	850	850	850	850	850
		12		850	850	850	850	850	850	850	840	810	780	750
		15			850	850	850	820	780	730	690	650	630	600

Serviceability Limit State [SLS] Pressure [Pa] - General														
Wind Class		Wind load Pa	System Height mm											
C	N		1590	1740	1890	2040	2190	2340	2490	2640	2790	2940	3090	3240
	1	400						10	10	10	10	12	12	12
	2	500					10	10	10	12	12	12	12	15
1	3	600				10	10	10	12	12	12	12	15	15
1	3	700				10	10	10	12	12	15	15	15	15
1	4	800			10	10	10	12	12	12	15	15	15	15
2	4	900			10	10	10	12	12	15	15	15	15	
2	4	1000			10	10	12	12	12	15	15	15		
2	4	1100		10	10	10	12	12	15	15	15			
2	5	1200		10	10	12	12	12	15	15				
3	5	1300		10	10	12	12	15	15	15				
3	5	1400	10	10	10	12	12	15	15	15				
3	5	1500	10	10	10	12	12	15	15	15				
4	6	1600	10	10	12	12	12	15	15	15				
4	6	1700	10	10	12	12	15	15	15					
4	6	1800	10	10	12	12	15	15	15					
		1900	10	10	12	12	15	15	15					
		2000	10	10	12	15	15	15						
		2100	10	12	12	15	15	15						
		2100	10	12	12	15	15	15						
		2200	10	12	12	15	15	15						

		2300	10	12	12	15	15	15						
		2500	10	12	12	15	15							
		2600	10	12	12	15	15							
		2700	10	12	15	15	15							
		2800	12	12	15	15	15							
		2900	12	12	15	15	15							
		3000	12	12	15	15	15							
		3100	12	12	15	15								
		3200	12	12	15	15								
		3300	12	12	15	15								
		3400	12	12	15	15								
		3500	12	12	15	15								
		3600	12	12	15	15								
		3700	12	15	15	15								
Max Panel width [mm]		10	850	850	850	850	850	850	850	850	850	850	850	850
		12		850	850	850	850	850	850	850	840	810	780	750
		15			850	850	850	820	780	730	690	650	630	600

GLASS OPTIONS

Description		A Grade Toughened Safety Polished AS1288		
Thickness Option mm		10	12	15
Weight kg/m ²		26	32	40
Finish:	Clear	✓	✓	✓
	Low-iron	✓	✓	✓
	Tint- Grey	✓	✓	
	Low-e	✓		

Note:

Glass size = system height mm less 240mm

GLASS OPTIONS

Description		A Grade Toughened Safety Polished AS1288		
Thickness Option mm		10	12	15
Weight kg/m ²		26	32	40
Finish:	Clear	✓	✓	✓
	Low-iron	✓	✓	✓
	Tint- Grey	✓	✓	
	Low-e	✓		

Note:

Glass size = system height mm less 240mm

Max